

NOTICE OF EXPRESS MAILING

Express Mail Mailing Label Number: EM175209223US

Date of Deposit with USPS: June 17, 1998

Person making Deposit: Timothy W. Ricks

APPLICATION FOR LETTERS PATENT

for

**SPEAKER APPARATUS AND A COMPUTER  
SYSTEM INCORPORATING SAME**

Inventor:  
Jeffrey A. Bull

Attorney:  
Joseph A. Walkowski  
Registration No. 28,765  
Keith Hargrove  
Registration No. 34,836  
TRASK, BRITT & ROSSA  
P.O. Box 2550  
Salt Lake City, Utah 84110  
(801) 532-1922

0098779-06490  
862790-62286060

## BACKGROUND OF THE INVENTION

Another advance in subwoofer speaker design that has decreased the overall unit size is the utilization of ported chambers. The ported chambers also enhance the sound quality of the speaker system, as well as increase the speaker's responsiveness without



way to the market of personal computers. These include a right channel speaker, left channel speaker, and a monaural subwoofer unit. This requires three new components to be placed on the already crowded desktop of the computer user. Some users have gone to free up desk space by placing the CPU box on the floor or in another, out-of-the-way location. Such an approach is helpful in that additional desktop space is then available. Further, the user can place the subwoofer anywhere close, without it having to be optimally positioned as is required by the right or left speaker. This is <sup>because</sup> ~~since~~ the subwoofer does not produce stereophonic sound, but merely enhances the audio experience by providing the lower frequencies. It is well known to speaker design engineers that a single subwoofer system is more than adequate for reproducing the low frequency end of the audio spectrum needed for full audio reproduction.

Placing the CPU box under the desk or moving it away from the desktop, as well as moving the subwoofer system off the desktop and in <sup>an</sup> inconspicuous place, are good approaches to provide additional desktop real estate. Unfortunately, they create additional clutter either under the desk or in the separate storage area where the two units must be provided. Additionally, in shipping systems with multiple speaker~~s~~ sets, a larger shipping box is necessary to accommodate the typically much-larger subwoofer assembly than the two satellite speakers. This, in turn, incurs additional shipping costs as well as packing costs in terms of material and labor and time delays experienced in packing the unit.

Thus, what is needed is a satellite speaker system that overcomes the storage problems of the prior art by placing a subwoofer somewhere useful to the end user, and without taking up unnecessary space otherwise required by the user. This advantage would also overcome and reduce the costs of packing, shipping, and handling of an entire multi-media computer system. Further, such a subwoofer configuration should have the same acoustic benefits that ported subwoofer designs offer.

## BRIEF SUMMARY OF THE INVENTION

According to the present invention, an internal subwoofer apparatus is provided that is placed within the central processing unit (CPU) box of a computer system. The computer system may be a multi-media personal computer system that is capable of providing visual and audio recording and playback. The CPU box typically includes the motherboard that houses the main central processing unit as well as any ancillary processing chips needed for the computer system. The CPU box may also include memory modules such as short term random access memory, long term disk storage memory in the form of hard disk drives or removable floppy disk drive systems, as well as long term hard disk storage units such as CD-ROM systems. User input to the computer system may be provided by a keyboard and, optionally, a pointing device, such as a mouse or track ball. A monitor that displays video signals viewable by the user may be provided and be connected to the CPU and driven by either the main central processing unit or by a separate video processor, such as a video card. An audio system may be provided that includes a pair of satellite speakers serving as a first channel and a second channel, typically known as the right and left channels, and further includes a subwoofer unit located in the CPU box. The CPU box can be oriented in a tower configuration or a desktop configuration.

The subwoofer unit is mounted in a lower front portion of the box, if it is a tower box, or in a front side portion, if it is a desktop box. The subwoofer is ported to enhance audio reproduction and to conserve space. The speaker may be mounted in a down-fire position, meaning that the front of the speaker is mounted downwardly against a vibration and sound absorbing mat, while the reflecting sound echos within the chamber and then is enhanced through the port that opens to the front of the computer system. A separate volume control and on/off switch can be provided on the exterior of the CPU so as to either activate or deactivate the subwoofer within the CPU box. The switch and the subwoofer are coupled to the motherboard or, alternatively, to an audio sound card installed within a computer system.

## BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1 is a diagram representing a computer system that has multi-media capabilities and incorporates a subwoofer apparatus within the central processing unit box;

5 FIG. 2 is a cut-away schematic side view of the CPU box of FIG. 1;

FIG. 3 is a cut-away side view schematic diagram of the subwoofer apparatus of FIG. 2 shown in enlarged detail;

FIG. 4 depicts a side view schematic diagram of an alternative ported speaker system according to the present invention;

10 FIG. 5 depicts a connecting mechanism used to attach the subwoofer speakers enclosure shown in FIG. 3; and,

FIG. 6 depicts an alternative desktop CPU box incorporating the subwoofer apparatus according to the present invention.

## 15 DETAILED DESCRIPTION OF THE INVENTION

As depicted in FIG. 1, a computer system 10 includes a central processing unit (CPU) box 12, which is attached to a user input device, such as keyboard 14, and pointing device 16, an output device, such as monitor 18, and a pair of speakers 20. *computer system*  
*CPU box 10* further includes an integral woofer or subwoofer apparatus 22, found within ~~unit~~ *box* 12 and including a port 36 (see FIG. 2). CPU box 12 is shown in further detail in FIG. 2. CPU box <sup>12</sup>~~10~~ is configured in a tower configuration, which means it stands substantially in a vertically upright orientation, as opposed to a desktop configuration, which means to be in a substantially horizontally prone orientation as shown in FIG. 6.

25 *a* FIG. 2 is a <sup>*cross-sectional*</sup>~~cross-section~~ schematic diagram of CPU box 12 from FIG. 1.

*into air* > Within CPU box 12 there is speaker apparatus 22, which is held in place via fasteners 24. Fasteners 24 can comprise any type of mechanical fastener or chemical fastener such as screws, nylon clips, metal clips, adhesive, or friction fitting. CPU box 12 further includes a drive bay 26 that holds additional peripheral devices such as a floppy



substantially four-fifths the depth of the container for subwoofer 22 and a diameter of substantially one-fifth of the height of the container. Further, the port is placed at substantially one-fifth of the height of the top container portion and is centered across the front portion of the container. Thus, for a five inch cube container structure, port 36 will be four inches long with a diameter of substantially one inch and off-set substantially one inch from the top of the container for subwoofer 22. Additionally, the front portion of port 36 tapers outward to a diameter larger than the inner diameter of port 36. The second diameter is at a ratio of substantially 1.5:1 to the first diameter. In alternative embodiments, the container for subwoofer apparatus 22 may have a greater height, greater width, or greater depth. These dimensions are determined by the audio response desired by the speaker designer, as well as the space limitations found within the CPU box 12. For example, a container box that is seven inches high, six inches deep, and six inches in width, would allow for a larger speaker driver to be placed therein and a sound port having a larger volume because of the larger box dimensions.

FIG. 3 depicts an enlarged cross-sectional schematic diagram of subwoofer 22 found in FIG. 2. Subwoofer 22 includes two container units 42 and 44 that join together along the center line 48 (shown in ghosted form) to form a shell. The half shells formed by each of container units 42 and 44 make for quick and easy assembly. At least one or more speaker retaining elements 46 is located in each container unit 42, 44. These retaining elements 46 are designed so that speaker 34 can be quickly inserted into either container unit 42 or 44 and then assembly is completed upon the joining together of the two container units 42, 44 to form a shell. Retaining elements 46 can include any type of mechanical retainer such as, for example, spring clips, of metal or plastic, molded bridges or recesses that conform to the edge of speaker 34, or foam gaskets that wedge in place and provide additional sound dampening.

Once container units 42 and 44 are mated, a plurality of speaker fasteners 24<sup>12</sup> are inserted into subwoofer apparatus 22. A fastener 24 is inserted in each corner to secure speaker 34 in place as well as to hold units 42 and 44 together. Speaker 34 is



electrically connected to connector 40 that provides connection to the CPU located in CPU box 12. Speaker 34 is placed on motion and sound dampener 38. Motion and sound dampener 38 is made of a desired dampening material suitable for use in an acoustical speaker assembly. This can include a flexible rubber mat, a neoprene mat, or a fiberglass liner. Motion and sound dampener 38 serves to isolate speaker 34 from the vibrations encountered within CPU box 12 as well as to dampen any acoustic vibration caused by the speaker within the box and lessen interference in the performance of subwoofer 22. Additional acoustic dampening material may be lined within subwoofer 22 as desired.

FIG. 4 depicts a cross-sectional schematic diagram of an alternative embodiment of subwoofer 22. Subwoofer apparatus 22a includes a speaker 34 that is mounted in a direct facing position aligned with port 36. Behind speaker 34 is placed a sound dampening or acoustic vibration dampening material 38. This direct fire embodiment of FIG. 4 is designed such that port 36 is again <sup>size</sup> designed to have a diameter one-fifth of that <sup>of</sup> overall container of subwoofer 22a. The length of port 36 is 40% of the width of the container used for subwoofer 22a. In one embodiment, port 36 is centered in the subwoofer 22a, but can be moved up or down, or left or right as desired for acoustic optimization.

FIG. 5 depicts a view of separated containers 42 and 44 previously shown in FIGs. 3 and 4. They are self-aligned together and held in place with a friction alignment element 50. FIG. 6 depicts an alternative embodiment of the CPU box. In FIG. 6, a desktop box 112 has a speaker port 36 mounted to one side with disk drives 126 mounted in another side. A speaker controller switch 132 is also provided on <sup>the</sup> ~~this~~ front of the CPU box 112. Subwoofers 22 and 22a have a universal design that allows <sup>them</sup> it to be placed in either an upright or tower CPU box 12 of FIG. 1, or in a prone or desktop CPU box 112 as shown in FIG. 6. The only difference is that ~~retaining~~ <sup>fasteners</sup> elements 24 would secure the bottom of CPU box 112 from underneath in the embodiment of FIG. 6.

As will be apparent to those skilled in the art, <sup>a</sup> number of variations, <sup>and</sup> modifications of the described invention can also be used. Port shapes other than the round port thus depicted can be used, such as oval, elliptical, parabolic, square, rectangular, and other polygonal shapes. A single port can be replaced by two or more smaller ports. The subwoofer assembly can employ more than one speaker as well as more than one chamber. The absolute and relative sizes of the chambers, or enclosures, can be adjusted, particularly as needed to adjust the frequency response in coordination with the characteristics of other speakers, such as the midrange or tweeter speakers that are found in the satellite pair of speakers 20. Although standard conical speakers are depicted, other shapes of speakers can be used, such as parabolic, oval, elliptical, planar, and the like.

When speaker apparatus 22 is used as a subwoofer speaker, a low frequency bi-pass circuit is provided that cuts off signals having a frequency greater than about 100-120 hertz. A typical bypass filter is a resistor-capacitor circuit that is tuned to allow signal frequencies of 100-120 hertz or lower to pass to speaker ~~element~~ 34. If speaker ~~apparatus~~ 34 is to also reproduce higher frequencies, then a higher bypass filter would be required. Typically, in such an instance, the cut-off level would be at 200 Hertz and above. Thus, the RC circuit would be tuned to pass frequencies at 200 Hertz or below for output on speaker 34. It is, of course, understood that the cut off should not be taken as limited to 100 or 200 Hz, but may extend to a higher frequency as desired.

Although the invention has been described by <sup>a</sup> way of <sup>a</sup> preferred embodiment and various modifications and variations, other modifications and variations can also be used within the scope of the invention, the invention being defined by the appended claims and equivalence thereof.